Product datasheet

Specifications



PowerLogic Split Core Current Transformer - Type HA, for cable - 0150A / 5A

METSECT5HA015

Main

Range	PowerLogic
Product or component type	Current transformer
Product name	CT
Secondary current	5 A
Accuracy class	Class 1 at 1 VA
[In] rated current	150 A

Complementary

Current transformer type	Standard for cable Split core
Current transformer ratio	150/5
[Ith] conventional free air thermal current	180 A
Maximum safety factor	5
Permissible current	9000 A during 1 s
[Ue] rated operational voltage	< 720 V 50 Hz
[Ui] rated insulation voltage	3 kV 50 Hz for 1 minute
mounting mode	Clip-on
Width	Outside: 49 mm
Height	Outside: 80.1 mm
Depth	59 mm
Diameter	18.4 mm inner:
Electrical insulation class	Class E
Cable outer diameter	18.4 mm
Connections - terminals	Cable 2 cable(s) 0.5…1.5 mm² 0.5 m

Environment

Standards	DIN EN 60044-1 DIN EN 61869-1 DIN EN 61869-2 VDE 0414
Ambient air temperature for operation	-5…50 °C
Ambient air temperature for storage	-25…70 °C

Packing Units

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.0 cm
Package 1 Width	7.0 cm
Package 1 Length	7.0 cm
Package 1 Weight	310.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	16
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	5.216 kg

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**47 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**2 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.2 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**44 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.5 kg CO2 eq.**
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	Compliant
REACh Regulation	Free of Substances of Very High Concern above the threshold

Use Again

Repack and remanufacture

Recyclability potential, in %	**78**
End of life manual availability	End of Life Information
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**